

T2 LOGAN™

TICKET DISPENSER

T2 Logan is our next generation of PARCS, which communicates with the T2 Flex cloud-based software system. It is designed specifically for all gated parking solutions in vertical markets such as airports, healthcare, municipalities, property management, and universities.

The automated ticket dispenser issues barcode parking tickets and accepts a full range of access control credentials. Customizable voice annunciation prompts help guide the user with ticket issuance and facility entry process. With its new modern design, there are two large service doors and recessed user interface panel which allow for easy ticket refills and maintenance.

Key Features

- Large touch screen display (8.4”) makes it easy to read and enter information
- Thermal QR-coded tickets for high read rate
- Ability to print non-ingest ticket stock or optional ingest ticket stock
- Customizable voice prompts and messaging to guide user experience
- Full range of intercom system and video options for great customer experience and support
- Area imaging barcode scanner provides ability to use smartphones and pre-printed barcodes
- Universal gray or custom colors/wraps available
- Full offline functionality
- TCP/IP communication



ABOUT T2 SYSTEMS

T2 Systems is the largest parking technology provider in North America, with more than 24 years in the parking industry and currently serving thousands of parking professionals. T2 integrates the best people, processes, and technology for powerful, high performance, and secure parking solutions. Its open technology and processes are used to manage more than 200 million parking transactions for over 2 billion dollars annually across all 50 states and ten provinces in Canada. Customers rely on T2 for multi-space pay stations, permit management, enforcement, LPR, PARCS, business intelligence, vehicle counting, citation services, and event parking.

To learn more about T2's reliable and innovative parking technology solutions, visit T2systems.com.



TECHNICAL SPECIFICATIONS

Electrical

120V AC, 60 Hz; 15 amp max at 120V; I/O for gate vend, lane counts, reversible lanes

Mechanical

Thermal printer; color LCD display with vandal-resistant touch screen

Housing/Dimensions

Aluminum 8 Gauge (3.2 mm); 51"H x 22"W x 17"D; 125 lb; gray (RAL 9007) or custom color

Environment

Temperature -20°F to 122°F; humidity 10-95%

Standard Included Equipment

Multi-format prox reader; barcode/QR code imager

Factory Options

Common or customer-unique locks; standard gray (RAL 9007) or custom color; custom-branded vinyl wrap; AVI reader (externally mounted; connected) camera; intercom (multiple brands)